



Guarantee All Exams 100% Pass One Time!

2016 NEW Cisco CCNP Data Center 642-999 DCUCI:Implementing Cisco Data Center Unified Computing (DCUCI) Exam Questions and Answers RELEASED in Braindump2go.com Online IT Study Website Today!

2016 Braindump2go Valid Cisco 642-999 DCUCIA Exam Preparation Materials:

1. | Latest **175Q&As 642-999** PDF Dumps and VCE Dumps:

<http://www.braindump2go.com/642-999.html>

[Guarantee 100% Exam Pass!]

QUESTION 144

Which three parameters can be configured for a vHBA? (Choose three.)

- A. Enable persistent binding.
- B. Enable a hardware-based failover.
- C. Define a SAN pin group
- D. Assign a QoS policy.
- E. Define an MTU.
- F. Assign a MAC address.

Answer: ACD

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-1/b_UCSM_GUI_Configuration_Guide_2_1/b_UCSM_GUI_Configuration_Guide_2_1_chapter_011010.html

QUESTION 145

With Cisco UCS Manager, in which location do you monitor the chassis discovery process?

- A. CMC
- B. FSM

[642-999 Exam Dumps](#)

[642-999 Exam Questions](#)

[642-999 PDF Dumps](#)

[642-999 VCE Dumps](#)

<http://www.braindump2go.com/642-999.html>



Guarantee All Exams 100% Pass One Time!

- C. CDP
- D. DME

Answer: B

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_0100011.html

QUESTION 146

Which two protocols does the Cisco Integrated Management Controller support for managing standalone Cisco UCS -Series servers? (Choose two.)

- A. SoL
- B. IPMI
- C. IPMIv2
- D. SMASH CLP
- E. SNMPv3

Answer: CE

Explanation:

<http://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/at-a-glance-c45-737177.pdf>

QUESTION 147

Which three statements about what occurs when a Cisco UCS -Series Blade Server connects to the SAN across a fabric interconnect that is enabled in Fibre Channel NPV mode are true? (Choose three.)

- A. The server ports in F Port mode are pinned to the NP Ports.
- B. The E Ports are pinned to the E Ports on the fabric interconnect.
- C. Zoning is deployed on the fabric interconnect.
- D. The fabric interconnect is not assigned a Fibre Channel domain ID.
- E. Traffic that is received on the server ports in F Port mode from the server side is pinned to the NPIV-enabled uplink ports on the fabric interconnect.
- F. The fabric interconnect must have the Fibre Channel uplink port connected to the upstream switch F Port in NPIV mode that performs the Fibre Channel forwarder function.

Answer: ADE

QUESTION 148

You plan to implement FCoE on a Cisco UCS -Series server. Which option must you configure from the Cisco Integrated Management Controller GUI?

- A. a vNIC failover

[642-999 Exam Dumps](#)

[642-999 Exam Questions](#)

[642-999 PDF Dumps](#)

[642-999 VCE Dumps](#)

<http://www.braindump2go.com/642-999.html>

- B. a boot table entry
- C. NIV
- D. FIP mode

Answer: D

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/gui/config/guide/1-2-1/b_Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1/Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1_chapter9.html

QUESTION 149

Refer to the exhibit. Which tables correctly map the HIF ports to active FEX NIF ports on a Cisco UCS 2208X IOM in discrete pinning mode?

Table 1 1 - Fabric uplink interface active	All the HIF ports are pinned to the active uplink interface
Table 2 2 - Fabric uplink interfaces active	HIF Ports : 1,2,3,4 to uplink interface 1 HIF Ports: 5,6,7,8 to uplink interface 2
Table 3 4 - Fabric uplink interfaces active	HIF Ports: 1,8 to uplink interface 1 HIF Ports: 2,3 to uplink interface 2 HIF Ports: 6,7 to uplink interface 3 HIF Ports: 4,5 to uplink interface 4
Table 4 8 – Fabric uplink interfaces active	HIV Port: 1 to uplink interface 1 HIV Port: 2 to uplink interface 2 HIV Port: 3 to uplink interface 3 HIV Port: 4 to uplink interface 4 HIV Port: 5 to uplink interface 5 HIV Port: 6 to uplink interface 6 HIV Port: 7 to uplink interface 7 HIV Port: 8 to uplink interface 8

- A. Table 2 and Table 4
- B. Table 1 and T able 4
- C. Table 2 and Table 3
- D. Table 1 and Table 2
- E. Table 3 and Table 4

[642-999 Exam Dumps](#)

[642-999 Exam Questions](#)

[642-999 PDF Dumps](#)

[642-999 VCE Dumps](#)

<http://www.braindump2go.com/642-999.html>



Guarantee All Exams 100% Pass One Time!

Answer: B

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html

QUESTION 150

You have a Cisco UCS C-Series Server. What can you use to log the blade server statistics?

- A. the Cisco Integrated Management Controller log
- B. RADIUS
- C. LDAP
- D. the XML API

Answer: A

Explanation:

<http://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/datasheet-c78-733571.html>

QUESTION 151

You manage Cisco UCS -Series Rack-Mount Servers. Which three components can you upgrade by using the Cisco Host Upgrade Utility? (Choose three.)

- A. the LAN on motherboard
- B. the Cisco Integrated Management Controller
- C. the operating system images
- D. the system BIOS
- E. the fabric interconnects
- F. the FEX modules

Answer: ABD

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/lomug/2-0-x/b_huu_2_0_3/b_huu_2_0_3_chapter_01.html

QUESTION 152

Which three components are parts of the Cisco UCS -Series Blade Server software bundle? (Choose three.)

- A. the adapter firmware
- B. the Kernel and system firmware for fabric interconnects
- C. the BIOS firmware
- D. the IOM firmware
- E. the Cisco UCS Manager software
- F. the board controller firmware

[642-999 Exam Dumps](#)

[642-999 Exam Questions](#)

[642-999 PDF Dumps](#)

[642-999 VCE Dumps](#)

<http://www.braindump2go.com/642-999.html>



Guarantee All Exams 100% Pass One Time!

Answer: ACF

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/firmware-mgmt/gui/2-2/b_GUI_Firmware_Management_22/b_GUI_Firmware_Management_22_chapter_0100.html

QUESTION 153

Which slot(s) contain DIMMs in a 1DPC configuration on Cisco UCS blade server?

- A. 0
- B. 1 and 2 only.
- C. 1
- D. 2

Answer: C

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/hw/blade-servers/install/B200.html

QUESTION 154

Which destination(s) are valid for syslog messages for a Cisco UCS Fabric Interconnect?

- A. a file and monitor only
- B. the log, the monitor and syslog queue
- C. the console
- D. the console and log only
- E. a file
- F. the console, the monitor, and a file

Answer: F

Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/ucsm_syslog/b_Monitoring_Cisco_UCSM_Using_Syslog/b_Monitoring_Cisco_UCSM_Using_Syslog_chapter_010.html

[642-999 Exam Dumps](#)

[642-999 Exam Questions](#)

[642-999 PDF Dumps](#)

[642-999 VCE Dumps](#)

<http://www.braindump2go.com/642-999.html>