

- **Vendor: Cisco**
- **Exam Code: 642-999**
- **Exam Name: Implementing Cisco Data Center Unified Computing (DCUCI)**
- **New Questions**

**[Visit PassLeader and Download Full Version 642-999 Exam Dumps](#)**

**NEW QUESTION 144**

Which three parameters can be configured for a vHBA? (Choose three.)

- A. Enable persistent binding
- B. Enable a hardware-based failover
- C. Define a SAN pin group
- D. Assign a QoS policy
- E. Define an MTU
- F. Assign a MAC address

**Answer: ACD**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_1\\_chapter\\_011010.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-1/b_UCSM_GUI_Configuration_Guide_2_1/b_UCSM_GUI_Configuration_Guide_2_1_chapter_011010.html)

**NEW QUESTION 145**

With Cisco UCS Manager, in which location do you monitor the chassis discovery process?

- A. CMC
- B. FSM
- C. CDP
- D. DME

**Answer: B**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0\\_chapter\\_0100011.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_0100011.html)

**NEW QUESTION 146**

Which two protocols does the Cisco Integrated Management Controller support for managing standalone Cisco UCS -Series servers? (Choose two.)

- A. SoL
- B. IPMI
- C. IPMIv2
- D. SMASH CLP
- E. SNMPv3

**Answer: CE**

**Explanation:**

<http://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/at-a-glance-c45-737177.pdf>

**NEW QUESTION 147**

Which three statements about what occurs when a Cisco UCS -Series Blade Server connects to the SAN across a fabric interconnect that is enabled in Fibre Channel NPV mode are true? (Choose three.)

- A. The server ports in F Port mode are pinned to the NP Ports
- B. The E Ports are pinned to the E Ports on the fabric interconnect
- C. Zoning is deployed on the fabric interconnect
- D. The fabric interconnect is not assigned a Fibre Channel domain ID
- E. Traffic that is received on the server ports in F Port mode from the server side is pinned to the NPIV-enabled uplink ports on the fabric interconnect
- F. The fabric interconnect must have the Fibre Channel uplink port connected to the upstream switch F Port in NPIV mode that performs the Fibre Channel forwarder function

**Answer: ADE**

**NEW QUESTION 148**

You plan to implement FCoE on a Cisco UCS -Series server. Which option must you configure from the Cisco Integrated Management Controller GUI?

- A. a vNIC failover
- B. a boot table entry
- C. NIV
- D. FIP mode

**Answer: D**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/gui/config/guide/1-2-1/b\\_Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1/Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1\\_chapter9.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/gui/config/guide/1-2-1/b_Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1/Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1_chapter9.html)

**NEW QUESTION 149**

Refer to the exhibit. Which tables correctly map the HIF ports to active FEX NIF ports on a Cisco UCS 2208X IOM in discrete pinning mode?

<b>Table 1</b> 1 - Fabric uplink interface active	All the HIF ports are pinned to the active uplink interface
<b>Table 2</b> 2 - Fabric uplink interfaces active	HIF Ports : 1,2,3,4 to uplink interface 1 HIF Ports: 5,6,7,8 to uplink interface 2
<b>Table 3</b> 4 - Fabric uplink interfaces active	HIF Ports: 1,8 to uplink interface 1 HIF Ports: 2,3 to uplink interface 2 HIF Ports: 6,7 to uplink interface 3 HIF Ports: 4,5 to uplink interface 4
<b>Table 4</b> 8 – Fabric uplink interfaces active	HIV Port: 1 to uplink interface 1 HIV Port: 2 to uplink interface 2 HIV Port: 3 to uplink interface 3 HIV Port: 4 to uplink interface 4 HIV Port: 5 to uplink interface 5 HIV Port: 6 to uplink interface 6 HIV Port: 7 to uplink interface 7 HIV Port: 8 to uplink interface 8

- A. Table 2 and Table 4
- B. Table 1 and Table 4
- C. Table 2 and Table 3
- D. Table 1 and Table 2
- E. Table 3 and Table 4

**Answer: B**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html)

**NEW QUESTION 150**

You have a Cisco UCS C-Series Server. What can you use to log the blade server statistics?

- A. the Cisco Integrated Management Controller log
- B. RADIUS
- C. LDAP
- D. the XML API

**Answer: A**

**Explanation:**

<http://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/datasheet-c78-733571.html>

**NEW QUESTION 151**

You manage Cisco UCS -Series Rack-Mount Servers. Which three components can you upgrade by using the Cisco Host Upgrade Utility? (Choose three.)

- A. the LAN on motherboard
- B. the Cisco Integrated Management Controller
- C. the operating system images
- D. the system BIOS
- E. the fabric interconnects
- F. the FEX modules

**Answer: ABD**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/lomug/2-0-x/b\\_huu\\_2\\_0\\_3/b\\_huu\\_2\\_0\\_3\\_chapter\\_01.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/lomug/2-0-x/b_huu_2_0_3/b_huu_2_0_3_chapter_01.html)

**NEW QUESTION 152**

Which three components are parts of the Cisco UCS -Series Blade Server software bundle? (Choose three.)

- A. the adapter firmware
- B. the Kernel and system firmware for fabric interconnects
- C. the BIOS firmware
- D. the IOM firmware
- E. the Cisco UCS Manager software
- F. the board controller firmware

**Answer: ACF**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/firmware-mgmt/gui/2-2/b\\_GUI\\_Firmware\\_Management\\_22/b\\_GUI\\_Firmware\\_Management\\_22\\_chapter\\_0100.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/firmware-mgmt/gui/2-2/b_GUI_Firmware_Management_22/b_GUI_Firmware_Management_22_chapter_0100.html)

**NEW QUESTION 153**

Which slot(s) contain DIMMs in a 1DPC configuration on Cisco UCS blade server?

- A. 0
- B. 1 and 2 only.
- C. 1
- D. 2

**Answer: C**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/hw/blade-servers/install/B200.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/hw/blade-servers/install/B200.html)

**NEW QUESTION 154**

Which destination(s) are valid for syslog messages for a Cisco UCS Fabric Interconnect?

- A. a file and monitor only
- B. the log, the monitor and syslog queue
- C. the console
- D. the console and log only
- E. a file
- F. the console, the monitor, and a file

**Answer: F**

**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/ucsm\\_syslog/b\\_Monitoring\\_Cisco\\_UCSM\\_Using\\_Syslog/b\\_Monitoring\\_Cisco\\_UCSM\\_Using\\_Syslog\\_chapter\\_010.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/ucsm_syslog/b_Monitoring_Cisco_UCSM_Using_Syslog/b_Monitoring_Cisco_UCSM_Using_Syslog_chapter_010.html)

**NEW QUESTION 155**

.....

[Visit PassLeader and Download Full Version 642-999 Exam Dumps](#)